

HARNES, DICKEY & PIERCE, P.L.C.

Attorneys and Counselors
5445 Corporate Drive, Suite 400
Troy, Michigan 48098-2683
Phone: 248-641-1600
Fax: 248-641-0270
Ann Arbor, MI • Washington, D.C.

RECEIVED
CENTRAL FAX CENTER

FEB 02 2006

DATE: 2/02/06

NO. OF PAGES (INCLUDING THIS PAGE): 6

FOR: Jeffrey Zwartz

COMPANY: USPTO

FAX NO.: 571 273 8300

PHONE: 571 272 1758

ORIGINAL WILL FOLLOW BY:

- ☐ REGULAR MAIL
☐ OVERNIGHT MAIL
☐ COURIER
☒ WILL NOT FOLLOW

FROM: Damian Aguino

Please let us know by phone or fax if you do not receive any of these pages.

COMMENTS:

Replacement Amendments to the Claims for
10/788,618

*** NOTICE ***

The information contained in this telefax transmission is intended only for the individual to whom or entity to which it is addressed. It may also contain privileged, confidential, attorney work product or trade secret information which is protected by law. If the reader of this message is not the intended recipient, or an employee or agent responsible for delivering the message to the addressee, the reader is hereby notified that any dissemination, distribution, or copying of this communication is strictly prohibited. If you have received this communication in error, please immediately notify us by telephone and return the original message to us at the address above via the U.S. Postal Service. We will reimburse you for any reasonable expense (including postage) for the return of the original message.

Examiner Zweizig,

Please replace the Amendments to the Claims section with the following.

AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions and listings of claims in the application.

LISTING OF CLAIMS

1-10. (Cancelled)

11. (Currently Amended) A high swing cascode biasing circuit, comprising:

a current biasing circuit that generates a cascode bias and a main bias;

a frequency boosting circuit that receives said cascode bias and said main bias; and

a current mirror circuit that receives said main bias, wherein said frequency boosting circuit biases said current mirror and receives feedback from said current mirror.

12. (Original) The high swing cascode biasing circuit of Claim 11 wherein said current mirror circuit includes a first transistor, a second transistor and a first capacitance having one end connected between said first and second transistors and wherein said frequency boosting circuit biases a control terminal of said first transistor and receives feedback from said one end of said first capacitance.

13. (Original) The high swing cascode biasing circuit of Claim 12 wherein said frequency boosting circuit comprises:

a third transistor that has a control terminal that receives said cascode bias, a first terminal and a second terminal; and

a fourth transistor that has a control terminal that receives said main bias, a first terminal that communicates with said second terminal of said third transistor and a second terminal.

14. (Original) The high swing cascode biasing circuit of Claim 13 wherein said frequency boosting circuit comprises a second capacitance having one end that communicates with said first terminal of said third transistor and an opposite end that communicates with said second terminal of said third transistor and with said one end of said first capacitance.

15. (Original) The high swing cascode biasing circuit of Claim 14 wherein said frequency boosting circuit comprises an inverter that has an input that communicates with said first terminal of said third transistor and an output that communicates with said control terminal of said first transistor.

16. (Original) The high swing cascode biasing circuit of Claim 15 wherein said frequency boosting circuit comprises a first resistance having one end that communicates with said input of said inverter and an opposite end that communicates with said output of said inverter.

Serial No. 10/788,618

Page 2 of 5

17. (Original) The high swing cascode biasing circuit of Claim 12 wherein said first and second transistors are metal-oxide semiconductor field-effect transistors (MOSFETs).

18. (Original) The high swing cascode biasing circuit of Claim 12 wherein said feedback increases a transconductance of said first transistor.

19. (Original) The high swing cascode biasing circuit of Claim 11 wherein said frequency boosting circuit increases a bandwidth of said high swing cascode biasing circuit.

20. (Original) An Ahuja compensation circuit comprising the high swing cascode biasing circuit of Claim 11.

21. (Currently Amended) A high swing cascode biasing circuit, comprising:
current biasing means for generating a cascade bias and a main bias;
frequency boosting means for receiving said cascade bias and said main bias and for boosting a frequency response of said high swing cascode biasing circuit;
and

current mirror means for receiving said main bias, wherein said frequency boosting means biases said current mirror means and receives feedback from said current mirror means.

22. (Original) The high swing cascode biasing circuit of Claim 21 wherein said current mirror means includes a first transistor, a second transistor and first capacitance means for providing a first capacitance and having one end connected between said first and second transistors and wherein said frequency boosting means biases a control terminal of said first transistor and receives feedback from said one end of said first capacitance means.

23. (Original) The high swing cascode biasing circuit of Claim 22 wherein said frequency boosting means comprises:

a third transistor that has a control terminal that receives said cascode bias, a first terminal and a second terminal; and

a fourth transistor that has a control terminal that receives said main bias, a first terminal that communicates with said second terminal of said third transistor and a second terminal.

24. (Original) The high swing cascode biasing circuit of Claim 23 wherein said frequency boosting means comprises second capacitance means for providing a second capacitance and having one end that communicates with said first terminal of said third transistor and an opposite end that communicates with said second terminal of said third transistor and with said one end of said first capacitance means.

25. (Original) The high swing cascode biasing circuit of Claim 24 wherein said frequency boosting means comprises inverting means for inverting that has an input that communicates with said first terminal of said third transistor and an output that communicates with said control terminal of said first transistor.

26. (Original) The high swing cascode biasing circuit of Claim 25 wherein said frequency boosting means comprises first resistance means for providing a first resistance and having one end that communicates with said input of said inverter and an opposite end that communicates with said output of said inverter.

27. (Original) The high swing cascode biasing circuit of Claim 22 wherein said first and second transistors are metal-oxide semiconductor field-effect transistors (MOSFETs).

28. (Original) The high swing cascode biasing circuit of Claim 22 wherein said feedback increases a transconductance of said first transistor.

29. (Original) An Ahuja compensation circuit comprising the high swing cascode biasing circuit of Claim 21.